



Cola® Dry CAV

High-Performance and MSO-Free Drying Aid, Spray-Wax and Sealant

DESCRIPTION Proprietary Polymer Blend

LISTINGS US (TSCA), Canada (DSL/NDSL), Australia (AIC/AICS), China (IECSC), Korea (KECI), Philippines (PICCS), New Zealand (NZIoC), Taiwan (TCSI)

Cola® Dry CAV is a next-generation drying agent designed to replace traditional mineral seal oil (MSO)-based formulas and drying aids. It requires no complex formulation or blending, performs at standard 100% active MSO dilution rates up to 1:2500, but only requires simple dilution to be ready for use. Compared to MSO-based drying-aids this product offers superior surface properties and functionality utilizing a novel blend of silicone polymer technology and other multifunctional components.

Cola® Dry CAV provides a dual-action finish—immediate sheeting for spot-free drying, followed by durable, high-contact-angle water beading and gloss. Unlike standard MSO products that fade before you leave the lot, our coating delivers professional-grade endurance—lasting weeks at higher dilution and well over a month at lower dilution.

Engineered with a novel, multi-functional component, it allows for a reduction in total quaternary content without sacrificing performance and improved biodegradability, making it a cost-optimized choice for sustainable operations and water reclamation systems.

Cola® Dry CAV eliminates the fire hazards and separation issues common in MSO-based formulas, offering a 100% non-flammable alternative with superior shelf stability.

APPLICATIONS

- MSO-free drying aid
- Spray-wax for spot-free drying
- Clearcoat and sealants
- Wipe and shine
- Waterless car washes

Patent Pending

SPECIFICATIONS

Appearance @ 25°C	Clear Liquid
pH (as is)	4.0 – 6.0
Specific Gravity	1.01

Cola® Dry CAV One-For-All Applications

Applications	Usage
Ceramic Sealant	1:250–500 (16–8mL/car*)
Total Body Protectant	1:500–1000 (8–4mL/car*)
Clearcoat Protectant	1:500–1500 (8–2.5mL/car*)
Drying Agent	1:500–2500 (8–1.5mL/car*)
Windshield Rain-X® effect	5–10% for hand wipe, 2–4% for windshield wash
Tire Dressing (auto or hand)	Use as supplied or dilute up to 1:4

STORAGE / HANDLING

Cola® Dry CAV should be stored in closed containers. Store between 40–140°F. Never freeze the product. Shipped in 55 gallon poly drums (net weight 450 lb/204 kg) and totes (2250 lb/1020 kg). Typical shelf life is 24 months from date of manufacture. Safety Data Sheets may be found at www.colonialchem.com.



Colonial Chemical
Innovative Specialty Surfactants
www.colonialchem.com

Technical information contained herein is believed to be accurate. However, it is furnished without charge or obligation and is given and accepted at the recipient's sole risk. No guarantee of the accuracy of the information is made and the products discussed are sold without conditions or warranties expressed or implied. No warranties beyond the guarantee that Colonial Chemical products are manufactured to specs are expressed or implied, since the use of material is beyond our control. Purchasers should make their own tests and determine suitability of the product for their particular purposes. Nothing contained herein shall be considered a recommendation for any use that may infringe upon patent rights. Safety information regarding this product is contained in its Safety Data Sheet. © 2026, Colonial Chemical, Inc. All rights reserved. 4/26

*Assuming 1 gallon of dilution per car